


- Aanvullende eisen voor het aanbrengen van een leuning op een InfraCore dek:**
1. Belasting maximaal 3 kN/m op 1005mm hoogte,
  2. Spatiëring balusters maximaal 1,5m.



Type: T002A, FiberSmile Rond  
Onderwerp: Hekwerk  
Materiaal:  
Baluster:  
Staal S235, THV + 2-laags poedercoating  
of RVS A4, parelstralen  
Leuning: GVVK, Pultrusie, Max. 6m  
Bevestiging: 8.8 THV of RVS A4



Oostdijk 25, 3077 CP Rotterdam, Nederland +31 (0)10 476 58 58 info@fibercore-europe.com, www.fibercore-europe.com			
Opdrachtgever:		Gemeente Breda	
Werkordnummer:		21-534, GBRA.2101, Verkeersbrug Wolfsaardreef Breda	
Tekening nummer:		21-534-VWD-T002A-0-020-TEK-01-Hekwerk	Rev: 1.0
Naam:	Getekend	Gecontroleerd	Goedgekeurd
			Blad: 1 of 1
			Schaal: 1:50
			Formaat: A3
Datum:	19-3-2021	19-3-2021	Eenheid: mm

- Informatie:
1. Wijzigingen onder voorbehoud
  2. Aan de tekening kunnen geen rechten worden ontleend

Maten in mm	Tolerantie in mm
0-50	+/- 2
50-500	+/- 5
>500	+/- 10

© copyright FiberCore Europe BV. This document is the property of FiberCore Europe BV and may contain confidential and proprietary information. It may not be used for any purpose other than that which is supplied. This document may not be completely or partly disclosed, copied, duplicated or in any way made use of without prior written approval of FiberCore Europe BV.